K2 UL

Double-walled, robust PVC hose with UL approval



Applications	medical devices, cable protection, automation technology & robotics, printing machines, cleaning
Structure	PVC, grey / pebble grey (similar RAL 7032), opaque, steel wire / spring steel wire / coated / PVC
Temperature	-10°C up to 70°C
Properties	good flexibility, good tensile strength, ultimate elongation, crush-resistant, good ozone- & UV-resistance, hydrolysis & microbe resistant, flame-retardant
Norms	flame-retardant according to UL 94 fire protection standard / V2





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
20	26,50	30	0,80	0,50	0,27800	4-2507-020-00/999
25	31,50	38	0,60	0,40	0,16700	4-2507-025-00/999
35	42,00	53	0,60	0,40	0,24100	4-2507-035-00/999
45	52,50	68	0,60	0,40	0,31500	4-2507-045-00/999

Ocono VACUFLEX GmbH | Hessenring 8-12 | 64546 Mörfelden-Walldorf | Germany | T +49 6105 93390 | vacuflex@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026