

VACUFLEX® VSM-SO2

Very smooth internal profile hose with very low flow resistance

Applications	vacuum cleaner, industrial vacuum cleaners, cleaning, seed conveying, dust extraction
Structure	TPO, black, opaque, profile helix / solid profile helix
Temperature	-50°C up to 60°C
Properties	excellent flexibility, very good low-temperature flexibility, corrugated outside, smooth inside, crush-resistant, good flexibility restoring force after compression or bending, excellent mechanical properties, especially for higher tensile forces



Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
25	33,00	50	0,60	0,60	0,13300	4-2106-025-00
32	40,50	70	0,50	0,50	0,29700	4-2106-032-00
38	48,00	95	0,40	0,40	0,33650	4-2106-038-00
40	50,00	105	0,40	0,40	0,35370	4-2106-040-00
50	61,00	120	0,25	0,25	0,49330	4-2106-050-00
51	62,00	120	0,25	0,25	0,49360	4-2106-051-00
60	72,00	140	0,20	0,20	0,62700	4-2106-060-00
63	75,00	148	0,19	0,19	0,62000	4-2106-063-00
70	81,00	165	0,17	0,17	0,69000	4-2106-070-00
75	87,00	180	0,16	0,16	0,74000	4-2106-075-00
80	92,00	200	0,15	0,15	0,79000	4-2106-080-00