GreenX Clearwater

High-pressure rubber water hose with an operating pressure of 20 bar. For the conveyance of fresh water, service water and non-corrosive media. Consistently reliable performance and very high durability. Abrasion-resistant, light- and ozone-resistant, age-resistant, flexible.



Applications irrigation, agriculture, municipal services, waste disposal vehicles

Structure EPDM, black, opaque

Temperature -10°C up to 100°C

Properties high pressure resistance, smooth outside, smooth inside, very good temperature resistance, good oil & petrol resistance, hydrolysis & microbe resistant, good ozone- & UV-resistance





Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
13	21,00	4,00	50	20,00	60,00	0,00	0,26000	0,00	40	2590130400
13	21,00	4,00	50	20,00	60,00	0,00	0,26000	0,00	20	2590130200
25	35,00	4,00	110	20,00	60,00	0,00	0,60000	0,00	40	2590250400

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026