

FLEXADUX® HT 1100 CL

Highly flexible clip-on hose for temperatures up to +1100°C

Applications	exhaust gas extraction, extraction systems, high temperature applications, automotive engineering
Structure	high temperature stainless steel fabric, grey / silver grey (similar RAL 7001), opaque, clip profile / multi-layer
Temperature	-50°C up to 1.100°C
Properties	good flexibility, excellent temperature resistance, with external abrasion protection spiral, flame-retardant



Inner Diameter (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
102	60	0,20	3,60	3	53323102-0300-000-00
152	90	0,09	4,90	3	53323152-0300-000-00
160	96	0,08	5,10	3	53323160-0300-000-00
200	120	0,05	13,20	6	53323200-0600-000-00
203	120	0,05	6,60	3	53323203-0300-000-00
203	120	0,05	13,20	6	53323203-0600-000-00
250	175	0,04	18,00	6	53323250-0600-000-00
250	175	0,04	9,00	3	53323250-0300-000-00
254	175	0,04	9,00	3	53323254-0300-000-00
305	210	0,02	11,70	3	53323305-0300-000-00
350	245	0,02	13,80	3	53323350-0300-000-00
407	280	0,01	17,40	3	53323407-0300-000-00
508	400	0,01	22,80	3	53323508-0300-000-00