

FLEXADUX® SIL II

Light weight, two-ply spiral tube made of silicone

- Applications** extraction systems, vehicle construction, steam extraction, granule drying, automation technology & robotics
- Structure** coated fabrics / silicone coated glass fabric, brown / red brown (similar RAL 8012), opaque, steel wire / spring steel wire / not coated / copper plated
- Temperature** -70°C up to 250°C, short term up to 300°C
- Properties** light weight, excellent flexibility, very good temperature resistance, , good chemical resistance



Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
19	21,60	19	2,80	0,65	0,74	4	50410019-0400-000-PL
25	28,20	25	2,80	0,65	0,88	4	50410025-0400-000-PL
32	35,20	32	2,80	0,65	0,96	4	50410032-0400-000-PL
35	38,20	35	2,60	0,60	1,12	4	50410035-0400-000-PL
38	41,20	38	2,60	0,60	1,20	4	50410038-0400-000-PL
41	44,20	41	2,40	0,58	1,28	4	50410041-0400-000-PL
44	47,20	44	2,40	0,58	1,34	4	50410044-0400-000-PL
46	49,20	46	2,40	0,58	1,28	4	50410046-0400-000-PL
51	54,74	51	2,40	0,53	1,40	4	50410051-0400-000-PL
55	58,74	55	2,30	0,53	1,64	4	50410055-0400-000-PL
57	60,74	57	2,30	0,53	1,68	4	50410057-0400-000-PL
60	63,74	60	2,20	0,53	1,84	4	50410060-0400-000-PL
63	66,74	63	2,20	0,48	1,92	4	50410063-0400-000-PL
70	73,74	70	2,20	0,44	2,08	4	50410070-0400-000-PL
76	79,74	76	2,20	0,43	2,28	4	50410076-0400-000-PL
80	83,74	80	2,10	0,40	2,44	4	50410080-0400-000-PL
83	86,74	83	2,10	0,40	2,52	4	50410083-0400-000-PL
90	93,74	90	2,00	0,40	2,72	4	50410090-0400-000-PL
102	106,20	102	1,90	0,35	3,56	4	50410102-0400-000-PL
108	112,20	108	1,90	0,35	3,24	4	50410108-0400-000-PL
114	118,20	114	1,80	0,35	3,56	4	50410114-0400-000-PL
120	124,20	120	1,50	0,25	3,76	4	50410120-0400-000-PL

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
127	131,70	127	1,40	0,25	4,00	4	50410127-0400-000-PL
130	134,70	130	1,40	0,25	4,20	4	50410130-0400-000-PL
140	144,70	140	1,30	0,19	4,44	4	50410140-0400-000-PL
152	157,20	152	1,20	0,15	4,80	4	50410152-0400-000-PL
160	165,20	160	0,90	0,15	5,08	4	50410160-0400-000-PL
165	170,20	165	0,90	0,14	5,24	4	50410165-0400-000-PL
178	183,20	178	0,80	0,14	5,24	4	50410178-0400-000-PL
203	208,20	203	0,70	0,09	6,60	4	50410203-0400-000-PL
230	235,20	230	0,60	0,07	7,60	4	50410230-0400-000-PL
254	259,20	254	0,50	0,07	8,54	4	50410254-0400-000-PL
305	310,20	305	0,30	0,04	10,28	4	50410305-0400-000-PL