GreenX Hydracord

High-pressure rubber water hose for an operating pressure of 30 bar. For conveying fresh water, service water, hot water and compressed air. Consistently reliable performance and extremely high durability. Abrasion-resistant, light- and ozone-resistant, ageing-resistant, oil-resistant, seawater-resistant, flexible and self-extinguishing – ASTM C-542



Applications	irrigation, waste disposal vehicles, municipal services, agriculture
Structure	CR, black, opaque
Temperature	-30°C up to 100°C
Properties	high pressure resistance, corrugated outside, smooth inside, excellent temperature resistance, good oil & petrol resistance, hydrolysis & microbe resistant, rot proof, good ozone- & UV-resistance; self-extinguishing





Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
10	18,00	4,00	45	30,00	90,00	0,00	0,21000	0,00	40	2510100400
13	21,00	4,00	50	30,00	90,00	0,00	0,26000	0,00	40	2510130400
19	27,00	4,00	80	30,00	90,00	0,00	0,40000	0,00	40	2510190400
22	32,00	5,00	100	30,00	90,00	0,00	0,51000	0,00	40	2510220400
25	35,00	5,00	160	30,00	90,00	0,00	0,66000	0,00	40	2510250400
38	51,00	6,50	250	30,00	90,00	0,00	1,17000	0,00	40	2510380400

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026