

APDatec 143

Flexible suction and pressure hose made of soft PVC with an integrated hard PVC spiral for conveying liquids

- Applications** agriculture, waste water, irrigation, waste disposal vehicles
- Structure** soft PVC, grey / graphite grey (similar RAL 7024), opaque, plastic spiral / rigid PVC
- Temperature** -25°C up to 60°C



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
51	61,00	5,10	160	4,50	13,50	0,88	0,96000	28,80	30	1430510300
63	75,50	6,00	200	4,00	12,00	0,88	1,30000	39,00	30	1430630300
76	88,40	6,10	250	3,50	10,50	0,88	1,70000	51,00	30	1430760300
80	93,00	6,50	260	3,00	9,00	0,88	1,75000	52,50	30	1430800300
90	103,40	6,70	260	3,00	9,00	0,88	2,15000	64,50	30	1430900300
102	116,20	7,30	320	3,00	9,00	0,88	2,60000	130,00	50	1431020300
110	125,50	7,50	350	2,70	8,00	0,88	3,00000	90,00	30	1431100200
120	136,00	8,00	400	2,50	7,00	0,88	3,40000	102,00	30	1431200200
127	143,60	8,30	420	2,30	7,00	0,88	3,80000	114,00	30	1431270200
133	150,00	8,50	450	2,00	6,00	0,88	4,00000	120,00	30	1431330200
152	170,40	9,00	500	1,80	5,50	0,88	4,70000	235,00	50	1431520200
160	178,80	9,40	640	1,50	4,50	0,88	5,30000	159,00	30	1431600200
203	229,20	13,00	1.015	1,30	4,00	0,88	9,40000	188,00	20	1432030200