OneFlat L dark blue

Light weight flat hose with a PVC double layer and woven polyester yarn inlay

Applications agriculture, irrigation, waste water, construction drying, construction machines

Structure PVC, blue, opaque

Temperature -20°C up to 65°C

Properties light weight, crush-resistant, can be driven over, high pressure resistance, smooth inside, smooth outside







Inner Diameter (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
32	4,00	12,00	0,17000	8,50	50	710320500
38	4,00	12,00	0,21000	10,50	50	710380500
40	4,00	12,00	0,21000	10,50	50	710400500
40	4,00	12,00	0,21000	21,00	100	710401000
50	4,00	12,00	0,28000	28,00	100	710501000
76	3,00	9,00	0,36000	18,00	50	710750500
100	3,00	9,00	0,60000	30,00	50	711000500
150	2,00	6,00	1,00000	50,00	50	711500500

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 23.11.2026