Tigerflex PLUS

Universal water hose for use in industry, construction and agriculture

Applications agriculture, irrigation, cleaning, construction machines, vehicle construction

Structure EPDM, black, opaque

Temperature -40°C up to 100°C

Properties very good temperature resistance, very good low-temperature flexibility, crush-resistant, high pressure resistance, weather proof, good ozone- & UV-resistance







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
13	20,60	3,80	50	20,00	60,00	0,21000	1,05	5	80901305
13	20,60	3,80	50	20,00	60,00	0,21000	2,10	10	80901310
13	20,60	3,80	50	20,00	60,00	0,21000	3,15	15	80901315
13	20,60	3,80	50	20,00	60,00	0,24500	4,90	20	80901320
13	20,60	3,80	50	20,00	60,00	0,24500	9,80	40	80901340
19	28,00	4,50	65	20,00	60,00	0,41400	8,28	20	80901920
19	28,00	4,50	65	20,00	60,00	0,41400	16,56	40	80901940
25	35,00	5,00	250	20,00	60,00	0,50000	20,00	40	80902540

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026