APDatec 630 N

Light weight and highly flexible warm air hose made from PVC coated polyester fabric

Applications tent heating, air supply, heating, construction drying, asbestos removal

Structure Neoprene® coated polyester fabric PVC coated polyester fabric, yellow, opaque

Temperature -24°C up to 150°C

Properties very good flexibility, excellent axial compressibility, good tensile strength, good ozone- & UV-resistance, hydrolysis & microbe resistant, weather proof, self-extinguishing







Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
305	310,00	0,25	153	0,10	0,36300	2,76	7,6	630305
425	430,00	0,25	212	0,10	0,68900	5,24	7,6	630425
525	530,00	0,25	262	0,10	0,98000	7,45	7,6	630525

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026