APDatec 823 Lactoflex

Applications in dairy technology

Applications	beverage production & conveying, agriculture, milk- & cheese production
Structure	soft PVC, transparent, cross braid
Temperature	-25°C up to 60°C
Properties	good flexibility, weather proof hydrolysis & microbe resistant, crush-resistant, high pressure resistance, smooth outside very smooth inside
Norms	material according to Food EU Directive (EC) No. 1935/2004 & Regulation (EC) No. 10/2011 for A, B, C, D1 | Tolerances in accordance with DIN 16940







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
25	34,00	4,50	220	8,00	24,00	0,50400	12,60	25	8230254525
28	36,00	5,00	245	8,00	24,00	0,62700	15,68	25	8230285025

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 19.11.2026