Ocono
Ruhrkunststoff

FLEXADUX® P-G-EX 1

Light weight and highly flexible exhaust hose made of TPE-coated Polyester fabric



Applications exhaust gas extraction, extraction systems, vehicle construction, air extraction, high temperature applications

Structure TPE coated polyester fabric, black / jet black (similar RAL 9005), opaque, plastic spiral / PA

Temperature -40°C up to 150°C, short term up to 170°C

Properties very good temperature resistance, very good flexibility, can be driven over, crush-resistant, good oil & petrol resistance, very good chemical resistance





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
38	48,00	0,40	75	0,70	3,31	10	29205038-1000-000-77
38	48,00	0,40	75	0,70	4,97	15	29205038-1500-000-77
40	50,00	0,40	80	0,65	3,46	10	29205040-1000-000-77
40	50,00	0,40	80	0,65	5,20	15	29205040-1500-000-77
51	61,00	0,40	90	0,50	11,05	15	29205051-1500-000-77
51	61,00	0,40	90	0,50	7,37	10	29205051-1000-000-77
60	70,00	0,40	95	0,40	5,00	10	29205060-1000-000-77
60	70,00	0,40	95	0,40	7,51	15	29205060-1500-000-77
65	76,00	0,40	100	0,35	6,44	10	29205065-1000-000-77
65	76,00	0,40	100	0,35	9,66	15	29205065-1500-000-77
70	81,00	0,40	105	0,20	6,88	10	29205070-1000-000-77
70	81,00	0,40	105	0,20	10,33	15	29205070-1500-000-77
76	87,00	0,40	115	0,15	7,42	10	29205076-1000-000-77
76	87,00	0,40	115	0,15	11,13	15	29205076-1500-000-77
80	91,00	0,40	160	0,12	11,67	15	29205080-1500-000-77
80	91,00	0,40	160	0,12	7,78	10	29205080-1000-000-77
90	101,00	0,40	175	0,12	8,67	10	29205090-1000-000-77
90	101,00	0,40	175	0,12	13,01	15	29205090-1500-000-77
102	113,00	0,40	190	0,10	9,11	10	29205102-1000-000-77
102	113,00	0,40	190	0,10	13,67	15	29205102-1500-000-77
110	121,00	0,40	210	0,10	9,78	10	29205110-1000-000-77
110	121,00	0,40	210	0,10	14,67	15	29205110-1500-000-77

Ocono Ruhrkunststoff GmbH | Weseler Str. 35 | 45478 Mülheim an der Ruhr | Germany | T +49 208 99910 | rk@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
115	126,00	0,40	220	0,10	10,20	10	29205115-1000-000-77
115	126,00	0,40	220	0,10	15,30	15	29205115-1500-000-77
120	131,00	0,40	230	0,09	10,62	10	29205120-1000-000-77
120	131,00	0,40	230	0,09	15,93	15	29205120-1500-000-77
127	139,00	0,40	250	0,08	11,33	10	29205127-1000-000-77
127	139,00	0,40	250	0,08	16,99	15	29205127-1500-000-77
140	152,00	0,40	280	0,07	12,42	10	29205140-1000-000-77
140	152,00	0,40	280	0,07	18,63	15	29205140-1500-000-77
152	164,00	0,40	300	0,06	13,43	10	29205152-1000-000-77
152	164,00	0,40	300	0,06	20,15	15	29205152-1500-000-77
160	172,00	0,40	320	0,06	14,10	10	29205160-1000-000-77
160	172,00	0,40	320	0,06	21,15	15	29205160-1500-000-77
180	192,00	0,40	380	0,04	15,79	10	29205180-1000-000-77
180	192,00	0,40	380	0,04	23,68	15	29205180-1500-000-77
250	262,00	0,40	500	0,02	21,67	10	29205250-1000-000-77

Ocono Ruhrkunststoff GmbH | Weseler Str. 35 | 45478 Mülheim an der Ruhr | Germany | T +49 208 99910 | rk@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026