

FLEXADUX® Hyp T EL CL

Highly flexible clip hose for suction of aggressive vapors, electrically conductive

Applications	paint mist extraction, paper production, solvent vapor extraction, pharmaceutical production, venting
Structure	coated fabrics / Hypalon® coated polyester fabric, black / jet black (similar RAL 9005), opaque, clip profile / multi-layer
Temperature	-40°C up to 175°C, short term up to 190°C
Properties	light weight, very good flexibility, very good temperature resistance, very good chemical resistance, electrically conductive
Norms	TRBS 2153, ATEX 2014/34/EU



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
76	86,00	0,40	45	0,60	0,17	0,00	3	03305076-0300-000-00
76	86,00	0,40	45	0,60	0,17	0,00	6	03305076-0600-000-00
102	112,00	0,40	60	0,50	0,10	0,00	3	03305102-0300-000-00
102	112,00	0,40	60	0,50	0,10	0,00	6	03305102-0600-000-00
127	137,00	0,40	75	0,32	0,06	2,53	3	03305127-0300-000-00
127	137,00	0,40	75	0,32	0,06	5,05	6	03305127-0600-000-00
152	162,00	0,40	90	0,22	0,04	0,00	6	03305152-0600-000-00
152	162,00	0,40	90	0,22	0,04	0,00	3	03305152-0300-000-00