APDatec 925 black

Single layer Polyamide tube of PA 11/12

Applications pneumatics, vehicle construction, compressors, automation technology & robotics, compressed air

Structure Polyether-Polyurethane, black, opaque

Temperature -35°C up to 80°C

Properties good temperature resistance, very high pressure resistance, smooth outside, smooth inside







Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
4	6,00	1,00	18	9,00	0,01900	1,90	100	9250061000
6	8,00	1,00	22	9,00	0,02900	2,90	100	9250081000
6	8,00	1,00	22	9,00	0,02900	1,45	50	925S0081050
8	10,00	1,00	25	9,00	0,02600	2,60	100	9250101000

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 19.11.2026