

VACUFLEX® KD-STRETCH PVC

Highly flexible Polyurethane hose with PU-coated spring steel wire

Applications	vacuum cleaner, cleaning, extraction systems, industrial vacuum cleaners, drying
Structure	soft PVC, black / jet black (similar RAL 9005), opaque, steel wire / spring steel wire / coated / PVC
Temperature	-10°C up to 70°C
Properties	excellent flexibility, good abrasion resistance, good flexibility restoring force after compression or bending, good compression ratio, very good resilience when pressed or twisted, hydrolysis & microbe resistant, weather proof, rot proof, good tensile strength, ultimate elongation



Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
25	30,00	25	0,55	0,43000	1-7006-025-00/999
30	35,00	30	0,50	0,51000	1-7006-030-00/999
32	37,00	32	0,50	0,54000	1-7006-032-00/999
38	43,00	38	0,45	0,65000	1-7006-038-00/999
40	45,00	40	0,45	0,91000	1-7006-040-00/999
44	49,00	55	0,45	1,39000	1-7006-044-00/999
51	56,00	51	0,40	1,16000	1-7006-051-00/999