FLEXADUX® NEO II

Light weight, two-ply spiral hose made of neoprene®

Applications extraction systems, vehicle construction, steam extraction, granule drying, automation technology & robotics

Structure Neoprene® coated glass fabric, black / jet black (similar RAL 9005), opaque, steel wire / spring steel wire / not coated / copper plated

Temperature -50°C up to 135°C, short term up to 150°C

Properties light weight, excellent flexibility, very good temperature resistance, , good chemical resistance







Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
32	35,20	32	2,50	0,58	0,72	4	50430032-0400-000-PL
38	41,20	38	2,40	0,58	0,84	4	50430038-0400-000-PL
51	54,74	51	2,40	0,53	1,14	4	50430051-0400-000-PL
55	58,74	55	2,30	0,53	1,20	4	50430055-0400-000-PL
63	66,74	63	2,20	0,46	1,42	4	50430063-0400-000-PL
70	73,74	70	2,20	0,46	1,74	4	50430070-0400-000-PL
76	79,74	76	2,10	0,44	1,88	4	50430076-0400-000-PL
80	83,74	80	2,10	0,40	1,96	4	50430080-0400-000-PL
83	86,74	83	2,10	0,40	2,04	4	50430083-0400-000-PL
90	93,74	90	2,00	0,40	2,20	4	50430090-0400-000-PL
102	106,20	102	1,80	0,35	2,44	4	50430102-0400-000-PL
114	118,20	114	1,70	0,30	3,14	4	50430114-0400-000-PL
127	131,70	127	1,50	0,21	3,44	4	50430127-0400-000-PL
152	157,20	152	1,10	0,17	4,40	4	50430152-0400-000-PL
178	183,20	178	0,80	0,13	5,20	4	50430178-0400-000-PL
203	208,20	203	0,60	0,10	5,56	4	50430203-0400-000-PL

Ocono Ruhrkunststoff GmbH | Weseler Str. 35 | 45478 Mülheim an der Ruhr | Germany | T +49 208 99910 | rk@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026