

FLEXADUX® P 3 PU AE

Medium weight and flexible Polyurethane hose

Applications	dosing, textile fiber extraction, agriculture, roof drainage, conveying technology
Structure	TPU / Polyether-Polyurethane, transparent, steel wire / spring steel wire / coated / PVC
Temperature	-40°C up to 100°C, short term up to 125°C
Properties	medium weight, very good abrasion resistance, smooth inside, good oil & petrol resistance, hydrolysis & microbe resistant
Optional	- antistatic ($R \leq 10^8 \text{ Ohm}$) - electrically conductive ($R \leq 10^4 \text{ Ohm}$)



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
20	26,00	0,80	30	2,30	0,70	1,78	10	35600020-1000-000-00
20	26,00	0,80	30	2,30	0,70	2,67	15	35600020-1500-000-00
25	31,00	0,80	38	2,50	0,80	2,18	10	35600025-1000-000-00
25	31,00	0,80	38	2,50	0,80	3,27	15	35600025-1500-000-00
32	38,00	0,80	48	2,40	0,75	4,11	15	35600032-1500-000-00
32	38,00	0,80	48	2,40	0,75	2,74	10	35600032-1000-000-00
38	44,00	0,80	57	2,20	0,70	3,22	10	35600038-1000-000-00
38	44,00	0,80	57	2,20	0,70	4,83	15	35600038-1500-000-00
40	47,00	0,90	60	2,10	0,60	3,92	10	35600040-1000-000-00
40	47,00	0,90	60	2,10	0,60	5,88	15	35600040-1500-000-00
50	57,00	0,90	75	1,90	0,40	4,85	10	35600050-1000-000-00
60	67,00	0,90	90	1,60	0,35	5,77	10	35600060-1000-000-00
60	67,00	0,90	90	1,60	0,35	8,66	15	35600060-1500-000-00
70	77,00	0,90	105	1,30	0,30	6,69	10	35600070-1000-000-00
70	77,00	0,90	105	1,30	0,30	10,04	15	35600070-1500-000-00
76	83,00	0,90	114	1,20	0,30	7,25	10	35600076-1000-000-00
76	83,00	0,90	114	1,20	0,30	10,87	15	35600076-1500-000-00
80	87,00	0,90	120	1,20	0,30	7,62	10	35600080-1000-000-00
80	87,00	0,90	120	1,20	0,30	11,43	15	35600080-1500-000-00
90	97,00	0,90	135	1,10	0,28	12,81	15	35600090-1500-000-00
90	97,00	0,90	135	1,10	0,28	8,54	10	35600090-1000-000-00
100	109,00	1,10	150	1,00	0,25	10,76	10	35600100-1000-000-00

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
100	109,00	1,10	150	1,00	0,25	16,14	15	35600100-1500-000-00
110	119,00	1,10	165	0,90	0,25	11,81	10	35600110-1000-000-00
110	119,00	1,10	165	0,90	0,25	17,71	15	35600110-1500-000-00
115	124,00	1,10	173	0,85	0,25	12,33	10	35600115-1000-000-00
115	124,00	1,10	173	0,85	0,25	18,49	15	35600115-1500-000-00
120	129,00	1,10	180	0,85	0,25	12,85	10	35600120-1000-000-00
120	129,00	1,10	180	0,85	0,25	19,28	15	35600120-1500-000-00
140	149,00	1,10	200	0,60	0,18	15,53	10	35600140-1000-000-00
140	149,00	1,10	200	0,60	0,18	23,30	15	35600140-1500-000-00
150	159,00	1,10	225	0,50	0,18	16,60	10	35600150-1000-000-00
160	169,00	1,10	240	0,40	0,16	17,66	10	35600160-1000-000-00
160	169,00	1,10	240	0,40	0,16	26,50	15	35600160-1500-000-00
175	184,00	1,10	260	0,35	0,16	19,26	10	35600175-1000-000-00
175	184,00	1,10	260	0,35	0,16	28,89	15	35600175-1500-000-00
180	189,00	1,10	270	0,30	0,15	19,80	10	35600180-1000-000-00
180	189,00	1,10	270	0,30	0,15	29,69	15	35600180-1500-000-00
200	209,00	1,10	315	0,25	0,13	21,93	10	35600200-1000-000-00
200	209,00	1,10	315	0,25	0,13	32,89	15	35600200-1500-000-00
215	228,00	1,50	340	0,20	0,12	30,53	10	35600215-1000-000-00
225	238,00	1,50	350	0,20	0,12	31,89	10	35600225-1000-000-00
225	238,00	1,50	350	0,20	0,12	47,84	15	35600225-1500-000-00
250	263,00	1,50	375	0,20	0,12	35,30	10	35600250-1000-000-00
250	263,00	1,50	375	0,20	0,12	52,94	15	35600250-1500-000-00
254	267,00	1,50	385	0,20	0,12	35,84	10	35600254-1000-000-00
300	313,00	1,50	450	0,15	0,10	42,10	10	35600300-1000-000-00