PleXus AT

PVC water hose, anti-kink design featuring a spiral-woven tricot fabric

Applications irrigation, agriculture, waste water, cleaning

Structure soft PVC, yellow, opaque, SMT knitting

Temperature -20°C up to 65°C

Properties smooth inside, smooth outside, good ozone- & UV-resistance, weather proof, phthalate-free







Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
12,5	16,80	2,15	65	10,00	30,00	0,13000	3,25	25	8340130250
12,5	16,80	2,15	65	10,00	30,00	0,13000	6,50	50	8340130500
19	24,40	2,70	90	7,00	21,00	0,23000	11,50	50	8340190500
19	24,40	2,70	90	7,00	21,00	0,23000	23,00	100	8340191000
19	24,40	2,70	90	7,00	21,00	0,23000	5,75	25	8340190250
25	31,60	3,30	125	6,00	18,00	0,39000	9,75	25	8340250250
25	31,60	3,30	125	6,00	18,00	0,39000	19,50	50	8340250500
25	31,60	3,30	125	6,00	18,00	0,39000	39,00	100	8340251000

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026