

PS-MEDIUM

Lightweight and highly flexible PVC hot-air hose

Applications	construction drying, tent heating, air supply, screed drying, asbestos removal
Structure	PVC coated polyester fabric, yellow, opaque, steel wire / spring steel wire / not coated / galvanized
Temperature	-20°C up to 70°C
Properties	excellent flexibility, , with outer wearstrip profile, hydrolysis & microbe resistant rot proof weather proof, compressible
Norms	flame-retardant according to DIN 4102 / B2
Optional	- antistatic (PS-ANTISTATIC) - with end rings permanently heat-sealed on both ends



Inner Diameter (mm)	Total Weight per Piece (kg)	Length (m)	Article Number
150	4,10	5	09801150-0500-000-00
150	6,15	7,5	09801150-0750-000-00
150	8,20	10	09801150-1000-000-00
203	4,00	5	09801203-0500-000-00
203	6,75	7,5	09801203-0750-000-00
203	9,00	10	09801203-1000-000-00
250	5,40	5	09801250-0500-000-00
250	8,10	7,5	09801250-0750-000-00
250	10,80	10	09801250-1000-000-00
305	6,45	5	09801305-0500-000-00
305	9,68	7,5	09801305-0750-000-00
305	12,90	10	09801305-1000-000-00
356	10,95	7,5	09801356-0750-000-00
356	14,60	10	09801356-1000-000-00
356	7,30	5	09801356-0500-000-00
400	10,70	5	09801400-0500-000-00
400	16,05	7,5	09801400-0750-000-00
400	21,40	10	09801400-1000-000-00
500	13,35	5	09801500-0500-000-00
500	20,03	7,5	09801500-0750-000-00
500	26,70	10	09801500-1000-000-00
600	22,20	5	09801600-0500-000-00

Inner Diameter (mm)	Total Weight per Piece (kg)	Length (m)	Article Number
600	33,30	7,5	09801600-0750-000-00
600	44,40	10	09801600-1000-000-00