VACUFLEX® KD-STRETCH PVC

Highly flexible PVC hose with PVC-coated spring steel wire




Applications industrial vacuum cleaners, vacuum cleaner, extraction systems, cleaning, cable protection

Structure soft PVC, black / jet black (similar RAL 9005), opaque, steel wire / spring steel wire / coated / PVC

Temperature -10°C up to 70°C

Properties excellent flexibility, good abrasion resistance, good flexibility restoring force after compression or bending, good compression ratio, very good resilience when pressed or twisted, hydrolysis & microbe resistant, weather proof, rot proof, good tensile strength, ultimate elongation





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
25	30,00	25	0,55	0,43000	1-7006-025-00/999
30	35,00	30	0,50	0,51000	1-7006-030-00/999
32	37,00	32	0,50	0,54000	1-7006-032-00/999
38	43,00	38	0,45	0,65000	1-7006-038-00/999
40	45,00	40	0,45	0,91000	1-7006-040-00/999
44	49,00	55	0,45	1,39000	1-7006-044-00/999
51	56,00	51	0,40	1,16000	1-7006-051-00/999

Ocono VACUFLEX GmbH | Hessenring 8-12 | 64546 Mörfelden-Walldorf | Germany | T +49 6105 93390 | vacuflex@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026