APDatec 105 ST

PVC hose reinforced with an impact-resistant rigid PVC spiral



Applications liquid manure spreading, agriculture, irrigation, waste water, trailing hose application

Structure soft PVC, green, transparent, plastic spiral / rigid PVC

Temperature -25°C up to 60°C

Properties very robust & resistant, reinforced with shock-resistant PVC spiral, crush-resistant, smooth outside, smooth inside, good chemical resistance, good ozone- & UV-resistance, weather proof





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
40	48,40	4,20	4,00	0,59	0,63000	0,71	1,00	10504001000
40	48,40	4,20	4,00	0,59	0,63000	0,43	0,6	10504000600
40	48,40	4,20	4,00	0,59	0,63000	0,57	0,8	10504000800

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 19.11.2026