VIDASPIR M 141

For industrial water, in agriculture and in pumping technology

Applications waste water, pump technology, agriculture, irrigation, waste disposal vehicles

Structure soft PVC, grey / silver grey (similar RAL 7001), opaque, plastic spiral / rigid PVC

Temperature -25°C up to 50°C

Properties good flexibility, good low-temperature flexibility, crush-resistant, very high vacuum resistance, very smooth inside







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
40	49,00	4,50	5,00	0,88	0,83500	25,05	30	1410400300
51	60,40	4,70	5,00	0,88	1,00000	30,00	30	1410510300
51	60,40	4,70	5,00	0,88	1,00000	50,00	50	1410510500
63	74,00	5,50	5,00	0,88	1,45600	43,68	30	1410630300
76	87,80	5,90	3,00	0,88	1,70000	51,00	30	1410760300
76	87,80	5,90	3,00	0,88	1,70000	85,00	50	1410760500
80	92,80	6,40	3,00	0,88	2,10000	63,00	30	1410800300
90	103,20	6,60	2,00	0,88	2,21000	66,30	30	1410900300
102	116,40	7,20	2,00	0,88	2,70000	81,00	30	1411020300
110	124,40	7,20	2,00	0,88	3,19000	95,70	30	1411100300
152	224,00	9,00	1,00	0,88	5,00000	125,00	25	1411520250
203	224,00	10,40	1,00	0,88	7,70000	77,00	10	1412030100
203	224,00	10,40	1,00	0,88	7,70000	154,00	20	1412030200

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026