

PVC 600

Flexible PVC hose with steel wire reinforcement

- Applications** extraction systems, air supply, air extraction, wood dust extraction, cable protection
- Structure** soft PVC, uncolored, transparent, steel wire / iron wire / not coated / copper plated
- Temperature** -10°C up to 70°C
- Properties** good flexibility, good compressibility, corrugated outside, good tensile strength, ultimate elongation, hydrolysis & microbe resistant, rot proof, weather proof



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
32	36,00	0,60	32	0,70	0,35	0,16400	5-5500-032-00/999
35	39,00	0,60	35	0,70	0,35	0,17900	5-5500-035-00/999
38	42,00	0,60	38	0,70	0,35	0,19300	5-5500-038-00/999
40	45,00	0,60	40	0,70	0,35	0,22800	5-5500-040-00/999
51	56,00	0,60	51	0,60	0,25	0,28800	5-5500-051-00/999
60	65,00	0,60	60	0,60	0,25	0,33700	5-5500-060-00/999
65	70,00	0,60	65	0,60	0,25	0,36400	5-5500-065-00/999
70	75,00	0,60	70	0,60	0,25	0,43200	5-5500-070-00/999
76	81,00	0,60	76	0,60	0,25	0,46800	5-5500-076-00/999
80	85,00	0,60	80	0,40	0,15	0,49200	5-5500-080-00/999
83	88,00	0,60	83	0,40	0,15	0,51000	5-5500-083-00/999
90	95,00	0,60	90	0,40	0,15	0,55200	5-5500-090-00/999
102	108,00	0,60	102	0,30	0,10	0,58000	5-5500-102-00/999
110	116,00	0,60	110	0,30	0,10	0,62500	5-5500-110-00/999
120	126,00	0,60	120	0,30	0,10	0,68000	5-5500-120-00/999
127	133,00	0,60	127	0,30	0,10	0,72000	5-5500-127-00/999
152	158,00	0,60	152	0,30	0,10	0,85900	5-5500-152-00/999
160	166,00	0,60	160	0,20	0,05	0,90300	5-5500-160-00/999
203	210,00	0,60	203	0,20	0,05	1,18700	5-5500-203-00/999