Smartflex SMT Comfort with fittings

5-layer garden hose with innovative SMT fabric with claw coupling



Applications	irrigation
Structure	soft PVC, grey, opaque, SMT knitting
Temperature	-15°C up to 65°C
Properties	excellent flexibility, good tensile strength, crush-resistant, can be driven over, kink-resistant, anti-torsion, very high pressure resistance, good ozone- & UV-resistance, hydrolysis & microbe resistant, weather proof, rot proof, phthalate-free





Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
12,5	17,40	2,45	65	14,00	42,00	0,14000	3,50	25	8010130250K
19	25,40	3,20	105	9,00	27,00	0,27000	6,75	25	8010190250K
19	25,40	3,20	105	9,00	27,00	0,27000	13,50	50	8010190500K

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 23.11.2026