Ocono
Ruhrkunststoff

EXXHAUST

Light weight and very flexible exhaust hose of TPE-coated Polyester fabric

Applications exhaust gas extraction, extraction systems, automotive engineering, vehicle construction, air extraction

Structure TPE coated polyester fabric, black / jet black (similar RAL 9005), profile helix / hollow profile helix

Temperature -40°C up to 200°C
*with proper exhaust gas routing and sufficient fresh air supply (approx. 50%).

Properties very good flexibility, very good temperature resistance, with outer wearstrip profile, good oil & petrol resistance, good tensile strength crush-resistant can be driven over



hydrolysis resistant · microbe-resistant · +120°C high temperature · air

made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
51	68,00	0,40	48	0,40	1,65	5	29605051-0500-000-77
51	68,00	0,40	48	0,40	2,47	7,5	29605051-0750-000-77
51	68,00	0,40	48	0,40	4,95	15	29605051-1500-000-77
51	68,00	0,40	48	0,40	3,80	10	29605051-1000-000-77
63	80,00	0,40	53	0,28	2,03	5	29605063-0500-000-77
63	80,00	0,40	53	0,28	4,80	10	29605063-1000-000-77
63	80,00	0,40	53	0,28	3,04	7,5	29605063-0750-000-77
63	80,00	0,40	53	0,28	6,09	15	29605063-1500-000-77
76	93,00	0,40	60	0,17	5,40	10	29605076-1000-000-77
76	93,00	0,40	60	0,17	2,44	5	29605076-0500-000-77
76	93,00	0,40	60	0,17	3,66	7,5	29605076-0750-000-77
76	93,00	0,40	60	0,17	7,32	15	29605076-1500-000-77
102	119,00	0,40	71	0,05	9,80	15	29605102-1500-000-77
102	119,00	0,40	71	0,05	13,07	20	29605102-2000-000-77
102	119,00	0,40	71	0,05	7,10	10	29605102-1000-000-77
102	119,00	0,40	71	0,05	3,27	5	29605102-0500-000-77
102	119,00	0,40	71	0,05	4,90	7,5	29605102-0750-000-77
127	144,00	0,40	100	0,04	4,06	5	29605127-0500-000-77
127	144,00	0,40	100	0,04	6,09	7,5	29605127-0750-000-77
127	144,00	0,40	100	0,04	12,19	15	29605127-1500-000-77
127	144,00	0,40	100	0,04	8,70	10	29605127-1000-000-77
152	169,00	0,40	110	0,03	4,86	5	29605152-0500-000-77

Ocono Ruhrkunststoff GmbH | Weseler Str. 35 | 45478 Mülheim an der Ruhr | Germany | T +49 208 99910 | rk@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
152	169,00	0,40	110	0,03	7,29	7,5	29605152-0750-000-77
152	169,00	0,40	110	0,03	14,57	15	29605152-1500-000-77
152	169,00	0,40	110	0,03	10,40	10	29605152-1000-000-77
203	220,00	0,40	155	0,01	19,44	15	29605203-1500-000-77
203	220,00	0,40	155	0,01	6,48	5	29605203-0500-000-77
203	220,00	0,40	155	0,01	9,72	7,5	29605203-0750-000-77
203	220,00	0,40	155	0,01	13,70	10	29605203-1000-000-77

Ocono Ruhrkunststoff GmbH | Weseler Str. 35 | 45478 Mülheim an der Ruhr | Germany | T +49 208 99910 | rk@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026