

GENESIS® MK II

Light weight flexible profile hose made of PE

Applications	blowing in insulation material, extraction systems, asbestos removal, swimming pool technology, construction machines
Structure	PE, translucent, plastic spiral / PE
Temperature	-40°C up to 60°C
Properties	very good chemical resistance, crush-resistant, ultimate elongation, good tensile strength, floatable, free of halogen & softeners



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
38	50,00	0,70	60	1,30	0,60	3,04	10	43100038-1000-000-00
38	50,00	0,70	60	1,30	0,60	4,55	15	43100038-1500-000-00
51	63,00	0,70	80	1,00	0,50	4,09	10	43100051-1000-000-00
51	63,00	0,70	80	1,00	0,50	6,13	15	43100051-1500-000-00
63	75,00	0,70	100	0,80	0,40	4,85	10	43100063-1000-000-00
63	75,00	0,70	100	0,80	0,40	7,27	15	43100063-1500-000-00
76	88,00	0,70	120	0,50	0,30	8,68	15	43100076-1500-000-00
76	88,00	0,70	120	0,50	0,30	5,79	10	43100076-1000-000-00
90	102,00	0,70	140	0,40	0,20	10,20	15	43100090-1500-000-00
102	114,00	0,70	160	0,30	0,20	7,67	10	43100102-1000-000-00
102	114,00	0,70	160	0,30	0,20	11,51	15	43100102-1500-000-00