VACUFLEX® VSM-SO2

Very smooth internal profile hose with very low flow resistance

Applications vacuum cleaner, industrial vacuum cleaners, cleaning, seed conveying, dust extraction

Structure TPO, black, opaque, profile helix / solid profile helix

Temperature -50°C up to 60°C

Properties excellent flexibility, very good low-temperature flexibility, corrugated outside, smooth inside, crush-resistant, good flexibility restoring force after compression or bending, excellent mechanical properties, especially for higher tensile forces







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
25	33,00	50	0,60	0,60	0,13300	4-2106-025-00
32	40,50	70	0,50	0,50	0,29700	4-2106-032-00
38	48,00	95	0,40	0,40	0,33650	4-2106-038-00
40	50,00	105	0,40	0,40	0,35370	4-2106-040-00
50	61,00	120	0,25	0,25	0,49330	4-2106-050-00
51	62,00	120	0,25	0,25	0,49360	4-2106-051-00
60	72,00	140	0,20	0,20	0,62700	4-2106-060-00
63	75,00	148	0,19	0,19	0,62000	4-2106-063-00
70	81,00	165	0,17	0,17	0,69000	4-2106-070-00
75	87,00	180	0,16	0,16	0,74000	4-2106-075-00
80	92,00	200	0,15	0,15	0,79000	4-2106-080-00

Ocono VACUFLEX GmbH | Hessenring 8-12 | 64546 Mörfelden-Walldorf | Germany | T +49 6105 93390 | vacuflex@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026