

PS-LIGHT

Light weight and highly flexible hot-air hose made of PVC

Applications	construction drying, tent heating, air supply, screed drying, asbestos removal
Structure	PVC coated polyester fabric, yellow, opaque, steel wire / spring steel wire / not coated / galvanized
Temperature	-20°C up to 70°C
Properties	excellent flexibility, , with outer wearstrip profile, hydrolysis & microbe resistant rot proof weather proof, compressible
Norms	flame-retardant according to DIN 4102 / B2
Optional	- stronger design - with welded end rings on both sides



Inner Diameter (mm)	Total Weight per Piece (kg)	Length (m)	Article Number
203	4,90	5	09804203-0500-000-00
203	7,35	7,5	09804203-0750-000-00
203	9,80	10	09804203-1000-000-00
254	6,05	5	09804254-0500-000-00
254	9,08	7,5	09804254-0750-000-00
254	12,10	10	09804254-1000-000-00
305	6,35	5	09804305-0500-000-00
305	9,53	7,5	09804305-0750-000-00
305	12,70	10	09804305-1000-000-00
356	7,65	5	09804356-0500-000-00
356	11,48	7,5	09804356-0750-000-00
356	15,30	10	09804356-1000-000-00
407	9,70	5	09804407-0500-000-00
407	14,55	7,5	09804407-0750-000-00
407	19,40	10	09804407-1000-000-00
425	9,00	5	09804425-0500-000-00
425	13,50	7,5	09804425-0750-000-00
425	18,00	10	09804425-1000-000-00
508	21,60	10	09804508-1000-000-00
508	10,80	5	09804508-0500-000-00
508	16,20	7,5	09804508-0750-000-00
610	16,65	5	09804610-0500-000-00

Inner Diameter (mm)	Total Weight per Piece (kg)	Length (m)	Article Number
610	24,98	7,5	09804610-0750-000-00
610	33,30	10	09804610-1000-000-00
700	19,05	5	09804700-0500-000-00
700	28,58	7,5	09804700-0750-000-00
800	21,75	5	09804800-0500-000-00
800	32,63	7,5	09804800-0750-000-00