VACUFLEX® VSM AS

Very smooth inside profile hose made of antistatic modified TPO

Applications vacuum cleaner, industrial vacuum cleaners, cleaning, grinding machines, textile fiber extraction

Structure TPO, black, opaque, profile helix / solid profile helix

Temperature -50°C up to 60°C

Properties smooth inside, corrugated outside, excellent flexibility, permanently antistatic, very good resilience when pressed or twisted







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
20	28,00	50	0,60	0,60	0,19240	4-1806-020-00
25	33,00	50	0,60	0,60	0,24000	4-1806-025-00
27	35,50	60	0,60	0,60	0,25630	4-1806-027-00
28	36,00	60	0,60	0,60	0,28550	4-1806-028-00
29	37,00	70	0,50	0,50	0,29610	4-1806-029-00
32	40,50	70	0,50	0,50	0,30860	4-1806-032-00
35	43,60	75	0,50	0,50	0,33492	4-1806-035-00
36	43,00	75	0,50	0,50	0,34605	4-1806-036-00
38	48,00	80	0,40	0,40	0,36882	4-1806-038-00
40	50,00	90	0,40	0,40	0,38231	4-1806-040-00
45	55,00	100	0,30	0,30	0,43073	4-1806-045-00
48	58,00	110	0,28	0,28	0,44886	4-1806-048-00
50	61,00	120	0,25	0,25	0,46810	4-1806-050-00
60	72,00	140	0,20	0,20	0,57903	4-1806-060-00
63	74,00	150	0,18	0,18	0,60519	4-1806-063-00
70	81,00	165	0,17	0,17	0,73000	4-1806-070-00
75	87,00	180	0,16	0,16	0,55100	4-1806-075-00
80	92,00	200	0,15	0,15	0,93646	4-1806-080-00

Ocono VACUFLEX GmbH | Hessenring 8-12 | 64546 Mörfelden-Walldorf | Germany | T +49 6105 93390 | vacuflex@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 19.11.2026