VACUFLEX® VSM-SO1

Very smooth inside profile hose made of modified TPO

Applications vacuum cleaner, industrial vacuum cleaners, cleaning, dust extraction, sprayers

Structure TPO, black / grey aluminium (similar RAL 9007), profile helix / solid profile helix

Temperature -50°C up to 60°C

Properties excellent flexibility, crush-resistant, can be driven over, very good chemical resistance, good flexibility restoring force after compression or bending







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
25	33,00	50	0,60	0,60	0,15030	4-1125-025-00
27	35,50	60	0,60	0,60	0,17040	4-1125-027-00
29	38,50	65	0,60	0,60	0,18270	4-1125-029-00
32	40,50	70	0,50	0,50	0,32700	4-1125-032-00
32	40,50	70	0,50	0,50	0,22900	4-1125-032-01
36	44,70	75	0,50	0,50	0,28907	4-1125-036-00
37	45,10	80	0,50	0,50	0,29500	4-1125-037-00
38	48,00	80	0,40	0,40	0,36230	4-1125-038-00
40	50,00	90	0,40	0,40	0,38140	4-1125-040-00
50	61,00	120	0,25	0,25	0,51630	4-1125-050-00
60	72,00	140	0,20	0,20	0,62660	4-1125-060-00
63	75,00	148	0,19	0,19	0,65457	4-1125-063-00
70	80,00	165	0,17	0,17	0,69000	4-1125-070-00
75	87,00	180	0,16	0,16	0,74000	4-1125-075-00
80	92,00	200	0,15	0,15	0,79000	4-1125-080-00

Ocono VACUFLEX GmbH | Hessenring 8-12 | 64546 Mörfelden-Walldorf | Germany | T +49 6105 93390 | vacuflex@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026