

### PleXus AT

- Applications** waste water, irrigation, agriculture, cleaning
- Structure** PVC / soft PVC, yellow, opaque, SMT knitting
- Temperature** -20°C up to 65°C
- Properties** smooth inside, smooth outside, good ozone- & UV-resistance, weather proof, phthalate-free



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
12,5	16,80	2,15	65	10,00	30,00	0,13000	3,25	25	8340130250
12,5	16,80	2,15	65	10,00	30,00	0,13000	6,50	50	8340130500
19	24,40	2,70	90	7,00	21,00	0,23000	23,00	100	8340191000
19	24,40	2,70	90	7,00	21,00	0,23000	5,75	25	8340190250
19	24,40	2,70	90	7,00	21,00	0,23000	11,50	50	8340190500
25	31,60	3,30	125	6,00	18,00	0,39000	9,75	25	8340250250
25	31,60	3,30	125	6,00	18,00	0,39000	19,50	50	8340250500
25	31,60	3,30	125	6,00	18,00	0,39000	39,00	100	8340251000