APDatec 46

Flexible spiral hose made of EVA. reinforced with shock resitant hard PP spiral, phthalate-free

Applications	pool & whirlpool, swimming pool technology, filter systems, water drain
Structure	EVA, uncolored, transparent, plastic spiral / PP
Temperature	-20°C up to 60°C
Properties	good flexibility, crush-resistant, good tensile strength, smooth inside, corrugated outside, phthalate-free, hydrolysis & microbe resistant, weather proof







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
32	40,00	0,60	120	0,59	0,23000	11,50	50	460320500
38	47,00	0,80	130	0,59	0,28000	14,00	50	460380500
50	60,00	0,90	150	0,59	0,43000	21,50	50	460500500

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 19.11.2026