

GENESIS® MK II

Light weight flexible profile hose made of PE

- Applications** blowing in insulation material, extraction systems, asbestos removal, swimming pool technology, construction machines
- Structure** PE, translucent, plastic spiral / PE
- Temperature** -40°C up to 60°C
- Properties** very good chemical resistance, crush-resistant, ultimate elongation, good tensile strength, floatable, free of halogen & softeners



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
38	50,00	0,70	60	1,30	0,60	3,04	10	43100038-1000-000-00
38	50,00	0,70	60	1,30	0,60	4,55	15	43100038-1500-000-00
51	63,00	0,70	80	1,00	0,50	4,09	10	43100051-1000-000-00
51	63,00	0,70	80	1,00	0,50	6,13	15	43100051-1500-000-00
63	75,00	0,70	100	0,80	0,40	4,85	10	43100063-1000-000-00
63	75,00	0,70	100	0,80	0,40	7,27	15	43100063-1500-000-00
76	88,00	0,70	120	0,50	0,30	8,68	15	43100076-1500-000-00
76	88,00	0,70	120	0,50	0,30	5,79	10	43100076-1000-000-00
90	102,00	0,70	140	0,40	0,20	10,20	15	43100090-1500-000-00
102	114,00	0,70	160	0,30	0,20	7,67	10	43100102-1000-000-00
102	114,00	0,70	160	0,30	0,20	11,51	15	43100102-1500-000-00