APDatec 105

Highly flexible PVC hose reinforced with shock resistant rigid PVC spiral



Applications	liquid manure spreading, agriculture, irrigation, waste water
Structure	soft PVC, green, transparent, plastic spiral / rigid PVC
Temperature	-25°C up to 60°C
Properties	very good flexibility, crush-resistant, smooth outside, smooth inside, good chemical resistance, good ozone- & UV-resistance, weather proof





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
19	25,60	3,30	76	7,00	0,59	0,27500	13,75	50	1050190500
25	32,00	3,50	100	7,00	0,59	0,36000	18,00	50	1050250500
32	39,00	3,50	128	6,00	0,59	0,46500	23,25	50	1050320500
38	45,40	3,70	152	4,00	0,59	0,56000	28,00	50	1050380500
40	47,40	3,70	160	4,00	0,59	0,63000	31,50	50	1050400500
45	52,40	3,70	160	4,00	0,59	0,66000	33,00	50	1050450500
50	58,40	4,20	200	4,00	0,59	0,82000	41,00	50	1050500500

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026