GENESIS® ToiVac N

Flexible and very heavy weight ducting made of PE, with tightly welded connection cuffs

Applications mobile toilets, sewage suction, waste disposal vehicles, waste water, sewage treatment plants

Structure PE, yellow / saffron yellow (similar RAL 1017), opaque, plastic spiral / PE

Temperature -40°C up to 60°C

Properties can be driven over, crush-resistant, good tensile strength, very high vacuum resistance, very good chemical resistance, weather proof, good ozone- & UV-resistance, hydrolysis & microbe resistant, rot proof







made in Germany

Inner Diameter (mm)	Wall Thickness (mm)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
51	1,30	0,95	17,23	18,3	43511051-1830-130-00
51	1,30	0,95	18,82	20	43511051-2000-130-00
51	1,30	0,95	23,49	25	43511051-2500-130-00
51	1,30	0,95	9,49	10	43511051-1000-130-00
51	1,30	0,95	14,16	15	43511051-1500-130-00
76	1,30	0,95	13,94	10	43511076-1000-130-00
76	1,30	0,95	20,76	15	43511076-1500-130-00
76	1,30	0,95	25,26	18,3	43511076-1830-130-00
76	1,30	0,95	27,57	20	43511076-2000-130-00
102	1,30	0,85	17,69	10	43511102-1000-130-00
102	1,30	0,85	26,32	15	43511102-1500-130-00

Ocono Ruhrkunststoff GmbH | Weseler Str. 35 | 45478 Mülheim an der Ruhr | Germany | T +49 208 99910 | rk@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026