APDatec 103

Very flexible and light weight PVC hose with shock-resistant hard PVC spiral

Applications pond technology, water drain, irrigation, waste water, filter systems

Structure soft PVC, black, opaque, plastic spiral / rigid PVC

Temperature -5°C up to 60°C

Properties very good flexibility, corrugated outside, smooth inside, , good ozone- & UV-resistance



hydrolysis resistant · microbe-resistant · liquids

made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
19	23,80	2,40	19	0,39	0,11000	3,60	30	1030190300
25	30,00	2,50	25	0,39	0,18000	1,80	10	1030250100
25	30,00	2,50	25	0,39	0,13000	5,40	30	1030250300
32	38,00	3,00	32	0,34	0,22000	2,20	10	1030320100
32	38,00	3,00	32	0,34	0,20500	6,60	30	1030320300
38	44,40	3,20	38	0,29	0,26000	2,70	10	1030380100
38	44,40	3,20	38	0,29	0,26000	8,10	30	1030380300
40	46,40	3,20	40	0,29	0,28000	2,80	10	1030400100
40	46,40	3,20	40	0,29	0,27000	8,40	30	1030400300
50	57,00	3,50	50	0,29	0,43500	12,60	30	1030500300

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.

Date: 19.11.2026