

VACUFLEX® K1Z-L PU IND ECO

Lightweight and highly flexible spiral hose made of polyester-polyurethane

Applications	extraction systems, dust extraction, wood dust extraction, air extraction, paint mist extraction
Structure	Polyester-Polyurethane, uncolored, transparent, steel wire / spring steel wire / not coated / copper plated
Temperature	-40°C up to 90°C, short term up to 125°C
Properties	light weight, very good flexibility, good abrasion resistance, good tensile strength, ultimate elongation, good ozone- & UV-resistance



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
32	36,00	0,40	36	0,60	0,35	0,13800	4-8600-032-10/999
35	39,00	0,40	39	0,60	0,35	0,15000	4-8600-035-10/999
38	42,00	0,40	42	0,60	0,35	0,16300	4-8600-038-10/999
40	44,00	0,40	44	0,60	0,35	0,17100	4-8600-040-10/999
42	46,00	0,40	46	0,60	0,35	0,17900	4-8600-042-10/999
45	49,00	0,40	49	0,60	0,35	0,19100	4-8600-045-10/999
50	54,00	0,40	54	0,60	0,35	0,21200	4-8600-050-10/999
51	55,00	0,40	55	0,40	0,25	0,21600	4-8600-051-10/999
55	59,00	0,40	59	0,40	0,25	0,23300	4-8600-055-10/999
60	64,00	0,40	64	0,40	0,25	0,25300	4-8600-060-10/999
65	69,00	0,40	69	0,40	0,25	0,27400	4-8600-065-10/999
70	74,00	0,40	74	0,40	0,25	0,28400	4-8600-070-10/999
76	80,00	0,40	80	0,30	0,20	0,35200	4-8600-076-10/999
80	84,00	0,40	84	0,30	0,20	0,37000	4-8600-080-10/999
83	87,00	0,40	87	0,30	0,20	0,38400	4-8600-083-10/999
90	94,00	0,40	94	0,30	0,20	0,41600	4-8600-090-10/999
100	104,00	0,40	104	0,20	0,10	0,46100	4-8600-100-10/999
102	106,00	0,40	106	0,20	0,10	0,47000	4-8600-102-10/999
110	114,00	0,40	114	0,20	0,10	0,50700	4-8600-110-10/999
120	124,00	0,40	124	0,20	0,10	0,55200	4-8600-120-10/999
125	130,00	0,40	130	0,20	0,10	0,73900	4-8600-125-10/999
127	132,00	0,40	132	0,20	0,10	0,75000	4-8600-127-10/999

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
130	135,00	0,40	135	0,20	0,10	0,76800	4-8600-130-10/999
140	145,00	0,40	145	0,20	0,10	0,82600	4-8600-140-10/999
150	155,00	0,40	155	0,10	0,06	0,88400	4-8600-150-10/999
152	157,00	0,40	157	0,10	0,06	0,89600	4-8600-152-10/999
160	165,00	0,40	165	0,10	0,06	0,94200	4-8600-160-10/999
175	180,00	0,40	180	0,10	0,06	1,03000	4-8600-175-10/999
180	185,00	0,40	185	0,10	0,06	1,05900	4-8600-180-10/999
200	206,00	0,40	206	0,10	0,06	1,17000	4-8600-200-10/999
203	209,00	0,40	209	0,10	0,06	1,19300	4-8600-203-10/999
225	231,00	0,40	231	0,10	0,06	1,32100	4-8600-225-10/999
250	256,00	0,40	256	0,05	0,02	1,92900	4-8600-250-10/999
280	286,00	0,40	286	0,05	0,02	2,15900	4-8600-280-10/999
300	306,00	0,40	306	0,05	0,02	2,31200	4-8600-300-10/999
350	356,00	0,40	356	0,05	0,02	2,69400	4-8600-350-10/999