APDatec 37

Protection hose made of silicone-coated glass fabric for extremely hot environment


Applications cable protection, automotive engineering, vehicle construction, paper production, hose protection

Structure silicone coated glass fabric, red, opaque

Temperature -54°C up to 260°C

Properties excellent temperature resistance, very good low-temperature flexibility, can be driven over, crush-resistant, flame-retardant





Inner Diameter (mm)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
8	0,08500	1,28	15	37008
10	0,10600	1,59	15	37010
13	0,14500	2,18	15	37013
16	0,19400	2,91	15	37016
19	0,24800	3,72	15	37019
22	0,27500	4,13	15	37022
25	0,30100	4,52	15	37025
29	0,30700	4,61	15	37029
32	0,32100	4,82	15	37032
35	0,34900	5,24	15	37035
38	0,44700	6,71	15	37038
41	0,46900	7,04	15	37041
44	0,47200	7,08	15	37044
51	0,54500	8,18	15	37051
57	0,59700	8,96	15	37057
64	0,63900	9,59	15	37064
70	0,65200	9,78	15	37070
76	0,77500	11,63	15	37076

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 19.11.2026