APDatec 550

Light weight profile hose made of rigid PVC


Applications welding gas extraction, dust extraction, ventilation, extraction systems, fume extraction

Structure rigid PVC, grey, opaque

Temperature -20°C up to 80°C

Properties light weight, very good low-temperature flexibility, very smooth inside, hydrolysis & microbe resistant, good chemical resistance







Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
32	36,00	2,00	0,28000	1,40	5	550032
50	54,00	2,00	0,32000	1,60	5	550050
75	79,00	2,00	0,46000	2,30	5	550075
80	84,00	2,00	0,53800	2,70	5	550080
100	104,00	2,00	0,60000	3,00	5	550100
125	129,00	2,00	0,80000	4,00	5	550125
150	154,00	3,00	1,05000	5,15	5	550150

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 12.11.2026